

ITEM		MODEL
		2160GH
General Capacity	Center height	10.62"
	Max. swing over bed	21.56"
	Max. swing over gap	26.77"
	Max. swing over cross slide	14.17"
	Distance between centers	59"
Main Spindle	Spindle nose	D1-8
	Spindle bore	3.34"
	Spindle speeds	25 ~ 1545 rpm 18 steps
Carriage	Cross slide travel	12.99"
	Compound rest travel	5.90"
	Tailstock	
	Tailstock spindle dia.	2.95"
	Tailstock spindle travel	6.69"
	Tailstock spindle taper	MT#5
Bed	Bed width	13.77"
	Treading	
	Leadscrew	4TPI or 6mm/pitch
	Metric pitch threads	0.5-7mm/pitch (24 kinds)
	Inch threads	4-56 TPI (36 kinds)
	Module pitch threads	0.25-3.5 (16 kinds)
	DP threads	8-112DP (36 kinds)
Feeding Range	Range of longitudinal feeds	0.002" ~ 0.035"/rev.
	Range of cross feeds	0.03-0.44mm/rev.
Motor	Main spindle motor	10HP
	Rapid feed motor	90W (opt.)
	Coolant pump motor	1/8HP
Net Weight		5940 lbs
Gross Weight		6600 lbs
Packing Dimensions		111" × 48" × 67"