

ITEM		MODEL
		2260L
General Capacity	Swing over bed	560 mm / 22"
	Swing over gap	788 mm / 31"
	Swing over cross slide	340 mm / 13.4"
	Distance between centers	1500 mm / 59.1"
	Width of bed	400 mm / 15.7"
Headstock	Spindle nose	D1 - 8 / D1 - 11 (Opt.)
	Spindle bore	85 mm / 115 mm (Opt.) / 3.3" / 4.5" (Opt.)
	Spindle speeds	15 ~ 1500 R.P.M. (12 steps) / 10 ~ 1000 R.P.M. (12 steps, Opt.)
	Taper of spindle bore	MT 7
Threading	Inch threads range	2 ~ 56 T.P.I.
	Metric threads range	P 0.5 ~ P 14
	Longitudinal feeds range	0.05 ~ 0.82 mm / .002" ~ 0.032"
	Cross feeds range	0.02 ~ 0.40 mm / 0.0008" ~ 0.016"
	Leadscrew diameter	38 mm / 1.5"
	Leadscrew pitch	4 T.P.I. or 6 mm / 0.24"
	Taper of tail center	MT 5
Carriage	Compound rest travel	200 mm / 7.9"
	Cross slide travel	375 mm / 14.8"
Tailstock	Tail spindle travel	165 mm / 6.5"
	Tail spindle diameter	85 mm / 3.3"
Power	Main drive motor	10 HP (7.5 KW) / 10HP (7.5 KW 6P Opt.)
	Coolant pump	1/8 HP (0.1 KW)
Machine Dimensions		290 x 103 x 126 cm / 114" x 41" x 50"
Packing Dimensions		300 x 115 x 194 cm / 118" x 45" x 76"
Net Weight		2550 kgs / 5512 lbs
Gross Weight		2650 kg / 5842 lbs