

SPECIFICATIONS		GH-1440 A
CAPACITY	Swing Over Bed	14"
	Swing Over Cross Slide	8 5/8"
	Swing In Gap	20"
	Distance Between Centers	40"
	Bed Width	7 1/8"
HEADSTOCK	Spindle Nose	D1-4
	Spindle Bore	1 1/2"
	Taper of Spindle	MT NO.5
	Spindle Speeds - Steps	16 (2 Speed Motor)
	Spindle Speeds - Range	45 ~ 1800 RPM
CARRIAGE	Cross Slide Travel	7"
	Compound Slide Travel	4"
THREADS & FEEDS	Inch Threads	4-112 TPI
	Metric Threads	0.45 ~ 7.5 mm
	Longitudinal Feeds	0.0012 ~ 0.0294"/rev
	Cross Feeds	0.0003 ~ 0.01"/rev
TAIL STOCK	Quill Diameter	2 3/4"
	Quill Travel	4 3/4"
	Quill Taper	MT NO.3
POWER	Spindle Drive Motor	3 HP (2 Speed)
	Voltage	220V AC / 3 PH
MACHINE WEIGHT & DIMENSION	Net Weight	1,650 LBS
	Shipping Weight	1,975 LBS
	Dimension (LxWxH)	72" x 31" x 49"



1529 Cottage Street Ashland, Ohio 44805 Toll Free:866-622-4488 Local: 419-281-4488
www.rmscnc.com

STANDARD ACCESSORIES:

- 6" 3 Jaw Chuck
- 8" 4 Jaw Chuck
- Steady/Follow Rest
- Full Length Splash Guard
- Coolant System
- Micro Bed Stop
- Face Plate
- 4 Way Tool Holder

OPTIONAL ACCESSORIES:

- Taper Attachment
- Taper Attachment Installation
- Lever Type 5C Collet Closer JFK
- Import Collet Closer
- Acu-Rite Digital Read-Out
- Sony Digital Read-Out
- Anilam Digital Read-Out
- Newall Digital Read-Out
- D.R.O. Installation
- Quick Change Tool Holder Made In USA
- Import Quick Change Tool Holder
- Single Phase Motor

Member Organizations:



A+ Since 2011

